



AGRABLOW S&D /10 180°C

QUALITY HOSE FOR HOT AIR SUCTION AND DELIVERY
FROM THE COMPRESSOR TO THE TRUCK TANK
HOCHFERTIGER HEISSLUFTKOMPRESSORSCHLAUCH



APPLICATION: suction and delivery of dry hot air from the compressor to the truck tank.

TUBE: white, smooth, atoxic EPR rubber compound.

REINFORCEMENT: high strength synthetic plies with steel spiral embedded.

COVER: black, smooth, cloth impression EPDM rubber, resistant to abrasion, ozone and weather.

WORKING TEMPERATURE: -40°C + 180°C (-40°F + 356°F).

ANWENDUNG: Saug- und Druckschlauch für trockene Heißluft vom Kompressor zum Tank.

SEELE: weiss, glatt, ungiftige EPR Gummi.

EINLAGEN: hochzähes synthetisches Cordgewebe und verdeckte Stahldrahtspirale.

DECKE: schwarz, glatt (mit Stoffimpression) EPDM Gummi, abrieb-, ozon- und witterungsbeständig.

BETRIEBSTEMPERATUR: -40°C + 180°C.

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	MAX LENGTH
mm	inch	mm	inch	Kg/m	bar	psi	bar	psi	mm	bar	m
25,0	1	36,0	1.27/64	0,74	10	150	30	450	100	0,9	40
38,0	1.1/2	49,0	1.15/16	1,12	10	150	30	450	150	0,9	40
42,0	1.21/32	53,0	2.3/32	1,25	10	150	30	450	170	0,9	40
51,0	2	63,0	2.1/2	1,70	10	150	30	450	200	0,9	40
63,5	2.1/2	76,0	3	2,30	10	150	30	450	250	0,9	40
76,0	3	90,0	3.17/32	2,75	10	150	30	450	300	0,9	40
90,0	3.17/32	104,0	4.3/32	3,79	10	150	30	450	360	0,9	40
102,0	4	116,0	4.9/16	4,15	10	150	30	450	400	0,9	40

Other diameters, pressure, ratings available on request. Technical data, structure and polymers subject to change without notice.
Andere Durchmesser und Drücke sind verfügbar auf Wunsch. Die technischen Daten, die Strukturen und die Polymeren können ohne vorherige Benachrichtigung geändert werden.

BRANDING / KENNZEICHNUNG:



AGRABLOW S&D/10 180°C

tubi
gomma
torino

COLOUR / FARBE:

White / Weib