

GEMINI 2

Colour: inside white, outside blue

Temperature range: -10°C + 60°C 14°F + 140°F

Features: PVC hose reinforced by antishock rigid PVC spiral. Inner PU layer abrasion resistant and food grade. Inside smooth, light, very flexible. Strong, resists to fatigue, weather and to most chemicals.



Applications: suction and delivery of alimentary products and liquids (including fatty foods) according to EC Directives and Regulations.* Stronger than netuno PU, thanks to its PU layer is suitable for transport of grain, animal feed, sugar and flour, whenever stronger abrasion resistance is needed. **Particularly suitable for transport of olive oil.** The antistatic version is available on request.

Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Working Pressure	Bursting Pressure	Vacuum	Bending Radius	Roll Length	Volume
mm	mm	mm	g/m	bar	bar	mH2O	mm	m	m ³
30	3,5	4,1	500	5,0	15	10	120	50	0,155
31,8	3,6	4,2	550	5,0	15	10	125	50	0,163
40	3,9	4,6	730	5,0	15	10	160	50	0,208
50	4,3	5,0	1000	4,0	12	9	200	50	0,312
50,8	4,3	5,0	1010	4,0	12	9	200	50	0,316
60	4,5	5,3	1250	4,0	12	9	240	50	0,462
63,5	4,7	5,5	1400	4,0	12	9	260	50	0,504
70	5,0	5,9	1600	3,0	9	9	280	50	0,605
76	4,9	5,8	1700	3,0	9	9	310	50	0,647
80	5,1	6,0	1850	3,0	9	9	320	50	0,721
90	5,3	6,2	2150	3,0	9	9	360	30	0,620
100	6,0	7,0	2700	3,0	9	8,5	410	30	0,770
102	6,0	7,0	2750	3,0	9	8,5	410	30	0,782