

### EOLO L

Colour: dark grey

Temperature range: -10°C +50°C

**Features:** plasticized PVC duct with antishock rigid PVC spiral. Perfectly smooth inside, outside corrugated. **More flexible and lighter than the Eolo it keeps unchanged the technical properties (wear, resistance and bending) thanks to the perfect balance between weight and mechanical resistance.** Resistant to atmospherical agents and to most chemicals.

**Applications:** suction of air, fumes, gasses, sawing, dust. Aerating and conditioning plants, woodworking plants etc. Resistant to low temperature.



Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Vacuum	Bending Radius	Roll Length	Volume
mm	mm	mm	g/m	mH2O	mm	m	m <sup>3</sup>
25	0,8	2,5	150	2,5	30	50	0,072
30	0,8	2,6	190	2,5	35	50	0,102
31,8	0,8	2,8	200	2	35	50	0,108
35	0,8	2,9	225	2	35	50	0,137
38,1	0,8	3,0	250	2	45	50	0,163
40	0,8	3,0	270	2	50	50	0,178
45	0,8	3,1	340	2	55	50	0,207
50	0,8	3,5	415	2	60	50	0,263
50,8	0,8	3,5	415	2	60	50	0,266
60	0,8	3,6	485	1,6	70	50	0,361
63,5	0,8	3,6	505	1,6	70	50	0,380
70	0,9	3,8	560	1,5	90	50	0,541
76,2	0,9	3,8	615	1,5	100	50	0,620
80	0,9	4,3	725	1,5	110	50	0,655
90	0,9	4,5	825	1,4	125	30	0,442
100	0,9	4,6	940	1,3	140	30	0,642
102	0,9	4,6	940	1,3	140	30	0,654
110	1,0	5,0	1065	1,2	150	30	0,746
120	1,0	5,0	1165	1	160	30	0,831
127	1,0	5,0	1230	1	170	30	0,900
130	1,0	5,0	1260	0,9	170	30	0,945
140	1,0	5,1	1405	0,9	175	30	1,041
151,5	1,1	5,2	1550	0,8	180	20	0,952
152,4	1,1	5,3	1545	0,8	180	20	0,958
160	1,1	6,0	1725	0,7	190	20	1,040
180	1,1	6,0	1940	0,4	300	20	1,228
200	1,1	6,0	2135	0,4	400	20	1,431
203,2	1,1	6,0	2135	0,4	400	20	1,453
250	1,2	6,8	3210	0,4	450	10	0,947
300	1,2	6,9	3895	0,3	1000	10	1,450